
APTIV

PRODUCT BRIEF

POWER SUPPLY UNIT (PSU)
POWER OUTPUT CONNECTOR



BENEFITS

- Compliant with OCP ORv3 48V power output connector specification
- Industry-leading contact normal force for minimum temperature rise
- Supports reliable power delivery for data centers, AI computing, battery backup and energy storage applications

FEATURES

- Staggered terminal contacts for lowest-in-class engage force
- Protective slots around ground terminals prevent snagging during handling
- Terminal Position Assurance (TPA) to protect against terminal back-out
- Press-fit threaded inserts for secure fastening
- Available as loose components, braided assembly, wired pigtail or customer-specific assembly

ELECTRICAL PERFORMANCE

Power Contacts	Temperature Rise per EIA 364-70 Method II; Max allowable T_{rise} : 30 °C
Operating Voltage	46-52 V DC
Contact Resistance	EIA 364-06, 0.55 mΩ max
Dielectric Withstand Voltage	1000 V DC per EIA 364-20, Method B
Current Rating	360 A continuous (still air) 500 A continuous (moving air) per ORv3 specification

MATERIALS

Power Contacts	High-conductivity copper
Housing	High-temperature thermoplastic, UL 94 V-0, halogen-free
Finish	Silver over nickel plating

CERTIFICATIONS

UL1977	Pending

MECHANICAL & ENVIRONMENTAL PERFORMANCE

Mating Force	120 N Max
Un-mating Force	Not less than 9.73 N Min
Mating Cycles	50 cycles
Vibration Rating	EIA 364-28 Test Conditions VII E
Thermal shock / humidity	EIA 364-32 Method A, Test Condition VII -55 °C to +105 °C EIA 364-31 Method IV
Sealing Class	Unsealed IP20
Touch-safe Rating	Finger-proof IP2XB
Operating Temperature Range	15 °C to +70 °C (unpowered) -40 °C to +105 °C (powered)
Temperature Life Test	EIA 364-17, Method A, Test Condition V; 125 °C, 500 hours
Mating Misalignment Tolerance	6.4 mm side-to-side gatherability
Mechanical Envelope and Keep-out Zones	Supports +/- 3 mm float horizontally and vertically
Busbar Thickness Compatibility	6.0 +/- 0.2 mm per ORv3 spec

APTIV.COM | © 2026 APTIV | ALL RIGHTS RESERVED